

Rustique 3 Casement Windows

DATA CARD



This data card outlines the standard specification and options available for the above product.

Please refer to the full consumer brochure for further information and product photography.

Rustique 3

Rustique 3

Rustique 3 Casement Windows Technical Specification

PVC-u Profile

Halo Rustique 70mm ovolo outer frame
Standard outer frame 56mm high / optional 72mm
Fully welded transoms and mullions (optional mechanical joints with dummy sashes)
82mm Rustique 3 triple glazed ovolo stepped sash
Steel reinforced
Variable bay poles available plus standard 90°, 135°, 150°
Mitred internal ovolo beads

Colours

White | Rosewood on Rosewood | Rosewood on White | Cherrywood on Cherrywood | Cherrywood on White | White W/ grain on White W/grain | Black W/grain on White W/grain | Black W/grain on White | Cream W/grain on Cream W/grain (Irish Oak on Irish Oak and Grey W/grain on White upon request only) | Sprayed to RAL colour of choice

Handles

Standard – White Maxim key locking handle
Optional Maxim handles available in – Black, Polished Gold, Polished Chrome, Satin Chrome, Smokey Chrome
Fab n' Fix Monkey Tail or Tear Drop available in Antique Black, Hardex Chrome, Hardex Gold, Hardex Graphite

Locking and Hinge System

Maco Mspag lock with 4 collared cams and 2 shoot bolts plus 2 anti-theft claws. Heavy duty, high security fire escape hinges with easi-clean facility

Glass Unit Options

Sashes and dummy sashes standard 44mm triple glazed units to A++ energy rating (optional 32mm triple glazed units in fixed panes)

Glazing Options

Clear or patterned glass | range of lead lite patterns
Internal 18mm or 25mm Georgian bar
Ovolo Ali-lock clip on Georgian bar inside and out

Ventilation

When specified 2000/4000 trickle vents can be fitted into extension sections on head of outer frame

Accreditations

Tested and approved to PAS24 enhanced security and PAS23 weather performance