

Declaration of Performance



Evolution Manufacturing Ltd.
Units 6-8 Eldon Way, Biggleswade, Bedfordshire, SG18 8NH
United Kingdom

13

DoP No: 2-12/06/2013

Evolution Storm1 Internally Glazed Casement Window,
Intended for use in domestic or commercial refurbishment or new building applications.

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

Watertightness: NPD

Dangerous Substances: None released under normal indoor use.

Resistance to wind load: NPD

Load-bearing capacity of safety devices: Pass, 350N when fitted (1)

Acoustic performance: NPD

Thermal transmittance: $\leq 1.6\text{W/m}^2\text{K}$

Radiation Properties: NPD

Air Permeability: NPD

A factory Production Control (FPC) system is established, documented and maintained in accordance with ISO 9001 certificate no FM505761

(1)Report No. 2370/7492989 dated 17.02.2010 for Safety & Security friction hinges with built in restrictor – BSI, Notified Test Body No 0086

(2)Thermal Transmittance calculation approved by Buildcheck Notified Test Body No:1806
Ref Report No:CU13238-1 dated 21/06/2013

R. GLIDDEN

Name (Print)

Signed

DIRECTOR

Position

29/6/2013 SG18 8NH

Date and Place of Issue